

MODEL

SG SERIES | SG15AV
INDUSTRIAL SPLASH RESISTANT SEALED MONITOR



Stylish gasket sealed splash resistant monitor or for wet environments such as processing plants.

SPECIFICATION

LCD Display	15" TFT LCD
Display Size	304 mm x 228 mm
Pixel Pitch	0.297 x .297
Max resolution	XGA 1024 X 768
Contrast Ratio	400:1
Brightness	250 cd/m2
Response Time	12 ms
Display Colors	16M
Viewing Angle	140 deg H / 120 deg V
PC Interface	Video: RGB analog 0.7V p-p Synch: TTL positive or negative
Plug Play	DDC1/2B compatible
Video	RCA composite
Microphone	n/a
Protective Glass Overlay	Anti-reflection coating
Power	12V, 4A external power adaptor
Dimensions	16" x 15.3" x 7.7" (408mm x 390mm x 195mm)
Weight	11.7 lb (5.3 kg) net

All specifications are subject to change without prior notice.

FEATURES

- Available in 15" TFT LCD
- Splash resistant monitor
- Total gasket seal
- Protective Vandal Proof Glass
- Frame and VESA chassis mounting
- VGA and Composite Video Inputs
- Detachable Hardwired remote control for OSD
- Optional touchscreen